Fast and Minimal-Solvent Production of Superinsulating Silica Aerogel Granulate

L. Huber¹, S. Zhao¹, W. J. Malfait¹, S. Vares², M. M. Koebel¹*

¹Empa, Laboratory for Building Energy Materials and Components, Überlandstrasse 129, 8600 Dübendorf, ²VTT Technical Research Center of Finland, Vuorimiehentie 5, Espoo, Finland

Silica aerogel superinsulation products have a tremendous growth potential, mainly for industrial and pipe insulation. However, the high production cost prevent the adoption of silica aerogel products outside of their established niche markets. A one-pot synthesis for silica aerogel granulate is presented that significantly decreases solvent use, production time, and global warming potential. The inclusion of the hydrophobization agent prior to gelation with a postgelation activation step, enables a complete production cycle of less than four hours at the lab scale for a solvent use close to the theoretical minimum. The one-pot aerogel granulate retains the exceptional properties associated with silica aerogel, mostly the thermal conductivity of 14.4 $mW \cdot m^{-1} \cdot K^{-1}$ for the pilot scale materials, about half that of standing air (26 mW·m⁻¹·K⁻¹).



Figure 1. Structure, properties, and surface chemistry of one-pot and commercial aerogel. A) Photograph, B) TEM image, C) SEM images, D) water contact angle (WCA), E) dynamic vapor sorption (DVS), F) FTIR spectra, G) 1H-29Si CP MAS NMR spectra, H) nitrogen sorption isotherms, I) pore size distributions.

[1] Lukas Huber, Shanyu Zhao, Wim J. Malfait et al., Angew. Chemie - Int. Ed., 2017, 56, 1-5