

Development of Coke- and sintering-resistant Ni/SiO₂-based dry reforming catalyst by depositing a thin layer of Al₂O₃ via ALD

S. Kim¹, A. Armutlulu¹, P. M. Abdala², D. Hosseini¹, C. R. Müller^{2*}, C. Copéret²

¹ETH Zürich, ²ETH Zurich

The dry reforming of methane, DRM ($\text{CH}_4 + \text{CO}_2 \rightarrow 2\text{CO} + 2\text{H}_2$), is a promising process to convert two greenhouse gases into a synthesis gas (H_2/CO), that is a key intermediate for liquid fuels synthesized via the Fischer-Tropsch process [1]. Due to its comparatively low price (when compared to noble metals) and high activity, Ni-based catalysts are attractive for DRM. The main deactivation mechanisms of Ni-based dry methane reforming (DRM) catalysts are sintering and coke deposition, the extent of coke deposition being critically affected by the size of the Ni particles [2, 3]. Thus, by controlling and stabilizing the Ni particle size Ni-based DRM catalysts that possess a high and stable activity can be realized. In this work, we have developed Al₂O₃-coated, SiO₂-supported Ni DRM catalysts using atomic layer deposition (ALD). Catalysts with different Al₂O₃-shell thicknesses were prepared. Coating of Ni nanoparticles with an Al₂O₃ shell increases appreciably the catalysts' resistance to sintering and coke formation when compared to unmodified SiO₂-supported Ni.

[1] K. Fujimoto, K. Omata, T. Nozaki, O. Yamazaki and Y. Han, *Energy Conversion and Management* **1992**, 33, 529-536.

[2] V. Kroll, H. Swaan and C. Mirodatos, *Journal of Catalysis* **1996**, 161, 409-422.

[3] J. Richardson and S. Paripatyadar, *Applied Catalysis* **1990**, 61, 293-309.